

Texture Cure Machine - Concrete Texture Curing Machine, HEM TC 1200



Standard Specifications for HEM TC 1200 Texture Cure

CAT C1.6 Diesel Engine -

- 35 HP (25.7 kW) Tier III
- enclosed engine compartment
- engine sound proofing

Hydraulic Oil Reservoir 31 gallon (117 liter)

Fuel Reservoir 16.6 gallon (63 liter)

Hydraulic Pump System

- (1) double stage hydraulic pump
- flow divider isolates right travel system from left travel system.

Main Frame

- superior structural strength
- 30 inch (76 cm) wide expanded metal walkway
- 20 inch (61 cm) deep tubular frame
- bolt together sectional design
- 12 ft. (3.65 m) main frame (paving width 12')
- 30 inch (76 cm) wide structural frame
- frame extensions available: 2 ft. (61 cm), 4 ft. (122 cm), 10 ft. (304 cm), custom sections
- 12 ft. - 45 ft. (3.65 m - 13.7 m) widths standard
- frame legs adjustable for 0 to 24 inch (0 - 61 cm) slabs

Rubber Track Drive

- proportional controls for infinite variability of speed
- direct hydraulic drive, no chains or sprockets
- 9.1 inch (230 mm) wide continuous rubber track
- 115 ft. (35 m) per minute maximum travel speed

Lower Work Platform

- lower level to assist with hand working of slab
- treated wood for durability and comfort
- located at bottom of bridge frame for easy access to concrete slab

Operator's Platform

- spray and travel system pressure gauges
- hydraulic controls: travel, cure sprayer, drag lift, auto steer
- operator's seat for safety and comfort
- engine controls on console
- safety railing for access to walk platform

Optional Equipment

(not included in base machine)

Hydraulic Burlap (or astro-turf) Drag

- lift controlled at operator's platform
- single lever control

Cure Spray System

- continuous return agitation, variable speed
- hydraulic control from operators platform
- standard 55 gallon (208 liter) drum carrier
- wind screen to reduce drift
- adjustable outside nozzle booms for slab edge coverage
- double filtration of cure material to reduce nozzle plugs
- non-drip, triple tip nozzles

Longitudinal Tining System

- hydraulically controlled from operators platform
- automatic steering suggested
- tines not included

Automatic Forward Steering System

- 1 hydraulic stringline sensor
- steer from right or left hand side of machine
- automatic and manual steering, controlled from operator's platform

Automatic Rear Steering System

- 1 hydraulic sensor

Cure Tote Rack

- framework for allowing the use of 250 gallon (950 liter) plastic cure container
- includes additional cure section and return hoses

Water System for Burlap Drag

- electric water pump with 25 gallon (95 liter)
- all required hoses and wiring
- spray pipe with fogging nozzle tips
- sediment strainer

Form Riding Wheels (in lieu of tracks)

Transport Axle

- hydraulic controls
- removable transport hitch

Frame Inserts without Spray

- 24 inch (61 cm)
- 48 inch (122 cm)
- 120 inch (3.04 m)

Frame Inserts with Spray Bar and Screen

- 24 inch (61 cm)
- 48 inch (122 cm)
- 120 inch (3.04 m)
- 1 m
- 2 m

* Material and specifications subject to change without notification

Additional Options Available : Consult our Authorized India Representative on below mentioned contact details



TC 1200 Texture Cure



Individual Solutions for all Your Paving Needs



Apollo Infratech Pvt. Ltd.

(an Apollo Infratech Group company)
Ahmedabad - Mehsana State Highway
Village : Rajpur, 382715, Dist. Mehsana, (Gujarat) INDIA.
Office (M) : +91 90990 71618
sales@apolloinfratech.com

Authorized India Representative :



www.apolloinfratech.com

Custom Solution to Your Paving Needs with Concrete Texture Curing Machine




Optional Equipment (not included in base machine)

- Hydraulic Burlap (or astro-turf) Drag
- 12 ft (3.65 m) Cure Spray System
- Longitudinal Tining System
- Automatic Forward Steering System
- Cure Tote Rack
- Water System for Burlap Drag
- Form Riding Wheels (in lieu of tracks)
- Frame Inserts without Spray
- Frame Inserts with Spray Bar and Screen
- Other Engines Available at Customers Request



TC 1200 Texture Cure



Authorized India Representative :



www.apolloinfratech.com

